

Marking
T.B.D
Electrical characteristics

Frequency	Characteristic Impedance Upper limit	Characteristic Impedance Lower limit	ATT	RL	NEXT	PS NEXT	ELFEXT	PS ELFEXT	PD
(MHz)	Zu (Ω)	Zl (Ω)	(dB/100m)	(dB Min)	(dB Min)	(dB Min)	(dB Min)	(dB Min)	(ns/100m Max)
4	115.2	86.8	3.74	23.0	78.0	75.0	78.0	75.0	552.0
8	112.6	88.8	5.24	24.5	78.0	75.0	75.9	72.9	546.7
10	111.9	89.4	5.86	25.0	78.0	75.0	74.0	71.0	545.4
16	111.9	89.4	7.41	25.0	78.0	75.0	69.9	66.9	543.0
20	111.9	89.4	8.29	25.0	78.0	75.0	68.0	65.0	542.0
25	112.9	88.5	9.29	24.3	78.0	75.0	66.0	63.0	541.2
31.25	114.1	87.7	10.41	23.6	78.0	75.0	64.1	61.1	540.4
62.5	118.3	84.5	14.88	21.5	75.5	72.5	58.1	55.1	538.6
100	121.9	82.0	19.02	20.1	72.4	69.4	54.0	51.0	537.6
150	125.7	79.6	23.56	18.9	69.8	66.8	50.5	47.5	536.9
200	128.8	77.6	27.47	18.0	67.9	64.9	48.0	45.0	536.5
250	131.5	76.0	30.97	17.3	66.4	63.4	46.0	43.0	536.3
300	131.6	76.0	34.19	17.3	65.2	62.2	44.5	41.5	536.1
600	131.6	76.0	50.10	17.3	60.7	57.7	38.4	35.4	535.5

* Cable that meet the requirements of the characteristic impedance are not required to be measured for return loss;
alternately cables that meet the return loss requirements are not required to be measured for characteristic impedance.
* If FEXT loss is greater than 90 dB, EL FEXT loss may not be calculated.

Revision history:
REV.0 2019.01.20

Prepared by: Micheas Shao
Approved by: Yang Ji
Date : 2019.01.20


Linkz International Limited

6/F, Photonics Centre, 2 Science Park East Avenue, Hong Kong Science Park, Shatin, Hong Kong.
Tel: (852) 2425 4399 Fax: (852) 2418 1627 Email: sales@linkzindustries.com Website: http://www.linkzindustries.com